

## SHUTTER REFERENCE GUIDE

Material	PVC		
Paint	VOC Compliant		
Application	Internal use only		
Stile	Butt, Rabbet, D Mould. Co Extruded (Square Aluminium Insert)		
Louvres	89mm, Co Extruded (Oval Aluminium Insert)		
Top and Bottom Rails	Extruded PVC (Min Depth 80mm)		
Mid Rail	76mm Extruded PVC		
Tilt Rod	Metal Hidden Tilt Rod		
T Post	Extruded PVC - Beaded		
Hinges	76mm Non-Mortise , White and Stainless Steel		
Frames - Beaded	Large L Frame, Small L Frame, Z Frame, U Channels, Sill (Unbeaded)		
Colours	Snow White, Bright White		
Mounting Methods	Hinged / Fixed / Removable		
Corner and Bay Posts	Yes		
Special Shapes	No		
Wet areas	Yes		
Sliding and Bi-Fold	No		
Factory Deductions Reveal Fit (L-Frame)	3.2mm from the Width and Height		
Factory Deductions Reveal Fit (Z Frame)	3.2mm from the Width and Height		
Critical Midrail*	5mm		
Non Critical Midrail	± 38mm		

## **Shutter Dimensions**

	Min. Width	Min. Drop	Max. Width	Max. Drop	Mid Rail Required	2 <sup>nd</sup> Mid Rail Required
Panels	250mm	325mm	920mm	3000mm	>1500mm Height	>2500mm Height
Frames	300mm	400mm	3600mm	3050mm		

<sup>\*</sup>If more than one midrail is required then only one midrail can be classed as critical.





## SHUTTER REFERENCE GUIDE







